



JUNIPER ROUTER SECURITY TECHNICAL IMPLEMENTATION GUIDE (STIG) OVERVIEW

27 April 2022

Developed by DISA for the DoD

Trademark Information

Names, products, and services referenced within this document may be the trade names, trademarks, or service marks of their respective owners. References to commercial vendors and their products or services are provided strictly as a convenience to our users, and do not constitute or imply endorsement by the Defense Information Systems Agency (DISA) of any non-Federal entity, event, product, service, or enterprise.

TABLE OF CONTENTS

	Page
1. INTRODUCTION	1
1.1 Executive Summary	1
1.2 Authority	
1.3 Vulnerability Severity Category Code Definitions	1
1.4 STIG Distribution	
1.5 SRG Compliance Reporting	
1.6 Document Revisions	
1.7 Other Considerations	
1.8 Product Approval Disclaimer	3
2. ASSESSMENT CONSIDERATIONS	4
2.1 Security Assessment Information	4
3. GENERAL SECURITY REQUIREMENTS	5
3.1 Juniper Router RTR Configuration	5
3.2 Juniper Router NDM Configuration	

LIST OF TABLES

	Page
Table 1-1: Vulnerability Severity Category Code Definitions	2

1. INTRODUCTION

1.1 Executive Summary

The Juniper Router Security Technical Implementation Guide (STIG) provides the technical security policies, requirements, and configuration details for the implementation of security concepts to Juniper routers. The Juniper Router STIG contains the following two STIG packages:

- Juniper Router RTR(Router) STIG
- Juniper Router NDM (Network Device Management) STIG

1.2 Authority

Department of Defense Instruction (DoDI) 8500.01 requires that "all IT [information technology] that receives, processes, stores, displays, or transmits DoD information will be [...] configured [...] consistent with applicable DoD cybersecurity policies, standards, and architectures." The instruction tasks that DISA "develops and maintains control correlation identifiers (CCIs), security requirements guides (SRGs), security technical implementation guides (STIGs), and mobile code risk categories and usage guides that implement and are consistent with DoD cybersecurity policies, standards, architectures, security controls, and validation procedures, with the support of the NSA/CSS [National Security Agency/Central Security Service], using input from stakeholders, and using automation whenever possible." This document is provided under the authority of DoDI 8500.01.

Although the use of the principles and guidelines in these SRGs/STIGs provides an environment that contributes to the security requirements of DoD systems, applicable NIST SP 800-53 cybersecurity controls must be applied to all systems and architectures based on the Committee on National Security Systems (CNSS) Instruction (CNSSI) 1253.

1.3 Vulnerability Severity Category Code Definitions

Severity Category Codes (referred to as CAT) are a measure of vulnerabilities used to assess a facility or system security posture. Each security policy specified in this document is assigned a Severity Category Code of CAT I, II, or III.

Table 1-1: Vulnerability Severity Category Code Definitions

	DISA Category Code Guidelines
CAT I	Any vulnerability, the exploitation of which will directly and
	immediately result in loss of Confidentiality, Availability, or Integrity.
CAT II	Any vulnerability, the exploitation of which has a potential to result in
	loss of Confidentiality, Availability, or Integrity.
CAT III	Any vulnerability, the existence of which degrades measures to
	protect against loss of Confidentiality, Availability, or Integrity.

1.4 STIG Distribution

Parties within the DoD and federal government's computing environments can obtain the applicable STIG from the DoD Cyber Exchange website at https://cyber.mil/. This site contains the latest copies of STIGs, SRGs, and other related security information. Those without a Common Access Card (CAC) that has DoD Certificates can obtain the STIG from https://public.cyber.mil/.

1.5 SRG Compliance Reporting

All technical NIST SP 800-53 requirements were considered while developing this STIG. Requirements that are applicable and configurable will be included in the final STIG. A report marked Controlled Unclassified Information (CUI) will be available for items that did not meet requirements. This report will be available to component authorizing official (AO) personnel for risk assessment purposes by request via email to: disa.stig_spt@mail.mil.

1.6 Document Revisions

Comments or proposed revisions to this document should be sent via email to the following address: disa.stig_spt@mail.mil. DISA will coordinate all change requests with the relevant DoD organizations before inclusion in this document. Approved changes will be made in accordance with the DISA maintenance release schedule.

1.7 Other Considerations

DISA accepts no liability for the consequences of applying specific configuration settings made on the basis of the SRGs/STIGs. It must be noted that the configuration settings specified should be evaluated in a local, representative test environment before implementation in a production environment, especially within large user populations. The extensive variety of environments makes it impossible to test these configuration settings for all potential software configurations.

For some production environments, failure to test before implementation may lead to a loss of required functionality. Evaluating the risks and benefits to a system's particular circumstances and requirements is the system owner's responsibility. The evaluated risks resulting from not

applying specified configuration settings must be approved by the responsible AO. Furthermore, DISA implies no warranty that the application of all specified configurations will make a system 100 percent secure.

Security guidance is provided for the DoD. While other agencies and organizations are free to use it, care must be given to ensure that all applicable security guidance is applied at both the device hardening level and the architectural level due to the fact that some settings may not be configurable in environments outside the DoD architecture.

1.8 Product Approval Disclaimer

The existence of a STIG does not equate to DoD approval for the procurement or use of a product.

STIGs provide configurable operational security guidance for products being used by the DoD. STIGs, along with vendor confidential documentation, also provide a basis for assessing compliance with cybersecurity controls/control enhancements, which supports system assessment and authorization (A&A) under the DoD Risk Management Framework (RMF). Department of Defense AOs may request available vendor confidential documentation for a product that has a STIG for product evaluation and RMF purposes from disa.stig_spt@mail.mil. This documentation is not published for general access to protect the vendor's proprietary information.

AOs have the purview to determine product use/approval in accordance with (IAW) DoD policy and through RMF risk acceptance. Inputs into acquisition or pre-acquisition product selection include such processes as:

- National Information Assurance Partnership (NIAP) evaluation for National Security Systems (NSS) (https://www.niap-ccevs.org/) IAW CNSSP #11
- National Institute of Standards and Technology (NIST) Cryptographic Module Validation Program (CMVP) (https://csrc.nist.gov/groups/STM/cmvp/) IAW Federal/DoD mandated standards
- DoD Unified Capabilities (UC) Approved Products List (APL) (https://www.disa.mil/network-services/ucco) IAW DoDI 8100.04

2. ASSESSMENT CONSIDERATIONS

2.1 Security Assessment Information

Juniper routers incorporate network security, branch and campus network services, WAN connectivity including Layer 2, and Layer 3 VPN/MPLS services. Hence, Juniper routers may be deployed to support various enterprise network functions. It is critical to assess these routers using both STIGs provided in the package to reduce the risk of the network being compromised. The Juniper Router RTR STIG and the Juniper Router NDM STIG contain the specific configuration guidance for the various functional network roles and the management of these devices.

3. GENERAL SECURITY REQUIREMENTS

3.1 Juniper Router RTR Configuration

The Juniper Router RTR STIG is used to configure the router to secure Layer 3 capabilities. This includes security requirements for unicast and multicast forwarding, routing protocols, data plane filtering, quality of service (QoS), and various IP network services.

3.2 Juniper Router NDM Configuration

The Juniper Router NDM STIG is used to configure the management plane functionality. This includes security requirements for implementing administrator access, logging of events and configuration changes, time management, and System Network Management Protocol (SNMP).