

UNCLASSIFIED



**CISCO ADAPTIVE SECURITY APPLIANCE (ASA)
SECURITY TECHNICAL IMPLEMENTATION GUIDE
(STIG) OVERVIEW**

05 January 2026

Developed by DISA for the DOD

UNCLASSIFIED

Trademark Information

Names, products, and services referenced within this document may be the trade names, trademarks, or service marks of their respective owners. References to commercial vendors and their products or services are provided strictly as a convenience to our users, and do not constitute or imply endorsement by the Defense Information Systems Agency (DISA) of any nonfederal entity, event, product, service, or enterprise.

TABLE OF CONTENTS

	Page
1. INTRODUCTION.....	1
1.1 Executive Summary.....	1
1.2 Authority.....	1
1.3 Vulnerability Severity Category Code Definitions.....	1
1.4 STIG Distribution.....	2
1.5 SRG Compliance Reporting	2
1.6 Document Revisions.....	2
1.7 Other Considerations.....	2
1.8 Product Approval Disclaimer.....	3
2. CONCEPTS AND TERMINOLOGY.....	4
2.1 Management Access.....	4
2.2 ASA FirePOWER	4
2.3 VPN STIG Terminology.....	4

UNCLASSIFIED**LIST OF TABLES**

	Page
Table 1-1: Vulnerability Severity Category Code Definitions	2

1. INTRODUCTION

1.1 Executive Summary

The Cisco Adaptive Security Appliance (ASA) Security Technical Implementation Guide (STIG) provides the technical security policies, requirements, and implementation details for applying security concepts to Cisco ASA devices such as the ASA 5500 series and the 5500-X series with FirePOWER Services.

The Cisco ASA STIG is a package of the following:

- Cisco ASA FW (Firewall) STIG.
- Cisco ASA VPN (Virtual Private Network Server) STIG.
- Cisco ASA IPS (Intrusion Prevention System) STIG.
- Cisco ASA NDM (Network Device Management) STIG.

1.2 Authority

Department of Defense Instruction (DODI) 8500.01 requires that “all IT [information technology] that receives, processes, stores, displays, or transmits DOD information will be [...] configured [...] consistent with applicable DOD cybersecurity policies, standards, and architectures.” The instruction tasks that DISA “develops and maintains control correlation identifiers (CCIs), security requirements guides (SRGs), security technical implementation guides (STIGs), and mobile code risk categories and usage guides that implement and are consistent with DOD cybersecurity policies, standards, architectures, security controls, and validation procedures, with the support of the NSA/CSS [National Security Agency/Central Security Service], using input from stakeholders, and using automation whenever possible.” This document is provided under the authority of DODI 8500.01.

Although the use of the principles and guidelines in these SRGs/STIGs provides an environment that contributes to the security requirements of DOD systems, applicable NIST SP 800-53 cybersecurity controls must be applied to all systems and architectures based on the Committee on National Security Systems (CNSS) Instruction (CNSSI) 1253.

1.3 Vulnerability Severity Category Code Definitions

Severity Category Codes (referred to as CAT) are a measure of vulnerabilities used to assess a facility or system security posture. Each security policy specified in this document is assigned a Severity Category Code of CAT I, II, or III.

Table 1-1: Vulnerability Severity Category Code Definitions

Category	DISA Category Code Guidelines
CAT I	Any vulnerability, the exploitation of which will directly and immediately result in loss of Confidentiality, Availability, or Integrity.
CAT II	Any vulnerability, the exploitation of which has a potential to result in loss of Confidentiality, Availability, or Integrity.
CAT III	Any vulnerability, the existence of which degrades measures to protect against loss of Confidentiality, Availability, or Integrity.

1.4 STIG Distribution

Parties within the DOD and federal government's computing environments can obtain the applicable STIG from the DOD Cyber Exchange website at <https://cyber.mil/>. This site contains the latest copies of STIGs, SRGs, and other related security information. Those without a Common Access Card (CAC) that has DOD Certificates can obtain the STIG from <https://public.cyber.mil/>.

1.5 SRG Compliance Reporting

All technical NIST SP 800-53 requirements were considered while developing this STIG. Requirements that are applicable and configurable will be included in the final STIG. A report marked Controlled Unclassified Information (CUI) will be available for items that did not meet requirements. This report will be available to component authorizing official (AO) personnel for risk assessment purposes by request via email to: disa.stig_spt@mail.mil.

1.6 Document Revisions

Comments or proposed revisions to this document should be sent via email to the following address: disa.stig_spt@mail.mil. DISA will coordinate all change requests with the relevant DOD organizations before inclusion in this document. Approved changes will be made in accordance with the DISA maintenance release schedule.

1.7 Other Considerations

DISA accepts no liability for the consequences of applying specific configuration settings made on the basis of the SRGs/STIGs. It must be noted that the configuration settings specified should be evaluated in a local, representative test environment before implementation in a production environment, especially within large user populations. The extensive variety of environments makes it impossible to test these configuration settings for all potential software configurations.

For some production environments, failure to test before implementation may lead to a loss of required functionality. Evaluating the risks and benefits to a system's particular circumstances and requirements is the system owner's responsibility. The evaluated risks resulting from not applying specified configuration settings must be approved by the responsible AO. Furthermore, DISA

implies no warranty that the application of all specified configurations will make a system 100 percent secure.

Security guidance is provided for the DOD. While other agencies and organizations are free to use it, care must be given to ensure that all applicable security guidance is applied at both the device hardening level and the architectural level due to the fact that some settings may not be configurable in environments outside the DOD architecture.

1.8 Product Approval Disclaimer

STIGs provide configurable operational security guidance for products being used by the DOD. STIGs, along with vendor confidential documentation, also provide a basis for assessing compliance with cybersecurity controls/control enhancements, which supports system assessment and authorization (A&A) under the DOD Risk Management Framework (RMF). Department of Defense AOs may request available vendor confidential documentation for a product that has a STIG for product evaluation and RMF purposes from disa.stig_spt@mail.mil. This documentation is not published for general access to protect the vendor's proprietary information.

AOs have the purview to determine product use/approval in accordance with (IAW) DOD policy and through RMF risk acceptance. Inputs into acquisition or pre-acquisition product selection include such processes as:

- National Information Assurance Partnership (NIAP) evaluation for National Security Systems (NSS) (<https://www.niap-ccevs.org/>) IAW CNSSP #11.
- National Institute of Standards and Technology (NIST) Cryptographic Module Validation Program (CMVP) (<https://csrc.nist.gov/groups/STM/cmvp/>) IAW federal/DOD mandated standards.

2. CONCEPTS AND TERMINOLOGY

2.1 Management Access

Management access to the Cisco ASA is via command line interface (CLI) using secure shell or the web-based ASA Security Device Manager (ASDM) using TLS as the transport protocol. Secure shell is the prevailing method for management access configuration commands and is provided in the check and fix content for the Firewall, VPN, and NDM STIGs. Network auditors also are dependent on viewing the configuration commands from the ASA running configuration.

2.2 ASA FirePOWER

The IPS STIG is based on the ASA FirePOWER module, which can be licensed for the ASA 5500-X series. The ASA FirePOWER module provides Next-Generation Intrusion Prevention System (NGIPS), Application Visibility and Control (AVC), URL filtering, and Advanced Malware Protection (AMP). Management to the FirePOWER module can be via the ASDM or the FirePOWER Management Center. Because the ASDM image is provided with the ASA with no further license requirements, the ASDM is used to provide the check and fix content for the IPS STIG.

2.3 VPN STIG Terminology

The requirements in the ASA VPN STIG are divided into three sections. Requirements applicable to all VPN implementations are in the first section. Requirements applicable only to site-to-site (i.e., LAN-to-LAN) VPN implementations are in the next section. The term “VPN gateway” is used to call out these requirements. The last section contains requirements that apply to remote access VPN implementations. The term “remote access VPN server” is used to call out these requirements.